

# Dolby® 118-I-BK Installation Subwoofer



The Dolby 118-I-BK is a high performance flyable subwoofer for use in cinema auditoriums and professional applications.

The subwoofer cabinet has integrated rigging points allowing the cabinet to be suspended from the ceiling or side wall making it perfect for use as a bass management surround speaker in Dolby Atmos rooms.

The 18" driver used in the 118-I-BK has a Neo magnet structure for light weight and a high-temperature voice coil with a large Xmech rating for reliable operation.

## Key features

- Angled woofers for a minimal front surface area
- 13-ply wood cabinet
- Extensive internal bracing
- M10-1.5 threaded inserts

## Applications

- Developed for a wide range of professional applications where the highest quality is required
- Designed to be flown to supplement main clusters

## Dolby 118-I-BK Installation Subwoofer

### Specifications\*

Operating range <sup>1</sup>	35 Hz - 160 Hz
Sensitivity (1 W @ 1 M) <sup>2</sup>	99 dB
Power handling <sup>3</sup>	600 W (64 V)
Maximum (calculated) 1 M	127 dB Cont. / 133 dB Peak
Nominal impedance	8 Ohms
Transducers	18" woofer
Input	Advanced spring-loaded input plate
Enclosure	13-ply wood
Rigging	(16) Rigging Points (M10 -1.5 threaded inserts)
Dimensions (unit)	20.24" H x 19.69" W x 34.7" D (51.4 x 50 x 88.2 cm)
Weight (unit)	82 lb (37.2 kg)
Dimensions (shipping)	25.2" H 24.8" W x 39.8" D (64 x 63 x 101 cm)
Weight (shipping)	97 lb (44 kg)

1. -6 dB in half-space conditions using required processing

2. Measured with 12 dB crest pink noise @ 2.83 Vrms in ground plane conditions with required HPF and LPF. Sensitivity interpolated to 1m

3. 6 dB crest pink noise for one hour with required HPF and LPF, calculated power based on minimum impedance

The English version of this document is the only legally binding version.  
Translated versions are not legally binding and are for convenience only.

\*Specifications are subject to change without notice.

