



SLS CS100MH Cinema Screen Channel Speaker System



CS100MH shown with CSB115
Low Frequency Modules



The CS100MH is a passive mid/hi screen channel cinema loudspeaker for auditoriums of 100-150 seats. It is also available with an optional passive crossover (PXO.CS2015) for single channel amplifier operation when used with the CSB115.

The high frequency section features a high performance PRD500 planar ribbon transducer designed and manufactured by SLS Audio. The unique design and properties of the planar ribbon driver delivers fast transient accuracy as well as an exceptionally smooth high frequency response delivering a more direct sound to the audience even with screen spreading. The midrange section uses 2 x 6.5" drivers that are horn-loaded for increased sensitivity.



SLS CS100MH Cinema Screen Channel Speaker System

KEY FEATURES

- PRD500 planar ribbon, high frequency driver delivers unsurpassed sound quality
- Open and transparent sound even at high SPL due to advanced transducer technology in all bandwidth sections
- 90 x 40 degree dispersion pattern (not including screen scattering)
- 13-ply 3/4" Baltic Birch cabinet construction
- Included U-Bracket for easy installation and aiming
- Optional passive crossover network for single channel amplifier operation (#PXO.CS2015) when used with the CSB115 LF module

SPECIFICATIONS*

• Operating Range	200Hz to 20kHz
• Sensitivity (1W@1M) ¹	96dB
• Horizontal Coverage	90degs -6dB ²
• Vertical Coverage	40degs -6dB ²
• Power Handling ³	180W (27V) AES/2
• Max SPL (calculated) 1M	119dB continuous/125dB peak
• Nominal Impedance	4 ohms
• Crossover Frequency	Passive
• Transducers	MF 6.5"x2 HF 5" PRD500 Ribbon Driver
• Input	Barrier Strip
• Dimensions	27.86" H x 14.67" W x 9.26" D (70.76 x 37.26 x 23.52 cm)
• Net Weight	44 lbs. (19.96 kg)
• Shipping Dimensions	18.5" x 13.4" x 31.1" (47 x 34 x 79 cm)
• Shipping Weight	49.6 lbs (22.5 kg)
• Enclosure	13 ply Baltic birch
• Rigging	U-Bracket (included) for CSB115 attachment
• Optional Accessories	PXO.CS2015 Crossover for use with CSB115
• Finish Options	Flat Black Latex

APPLICATIONS

- Developed for high performance cinema applications where the highest quality and intelligibility of sound is required
- Behind Screen LCR

*Due to product improvement research, SLS Audio reserves the right to make changes to existing products without notice.

1. A sine wave sweep is applied to a voltage level measured at the loudspeaker terminals corresponding to 1W@1M as referenced to the loudspeaker's nominal impedance and the measuring distance. SPL is measured in an anechoic environment in the loudspeaker's far field with the exception of subwoofers, which are measured in half space. Sensitivity is determined by a Log/Log averaging method from 315Hz to 16kHz in the anechoic environment. Subwoofers use the same method with the half space measurement, but within their specified operating bandwidth.

2. Averaged from 500Hz to 8kHz

3. AES established in accordance with AES/2-2003 standard.



Dolby Laboratories, Inc. 1275 Market Street, San Francisco, CA 94103-1410 USA dolby.com

Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories.
© 2018 Dolby Laboratories, Inc. All rights reserved.