



SLS CS118I-CM Cinema Subwoofer Module



The CS118I-CM is a single 18" subwoofer. It is a high-performance, front-loaded, vented box design with maximized low-frequency extension.

The 18" driver used in the CS118I-CM uses a high-mass magnet structure and a high-temperature voice coil that results in a power handling of 600W RMS.



SLS CS118I-CM Cinema Subwoofer Module

KEY FEATURES

- Ported, front-loaded driver design for high sensitivity
- Extended low frequency response
- 13-ply 3/4" Baltic Birch cabinet construction
- Extensive internal bracing
- (1) 600W RMS 18" driver
- Barrier strip input connection
- (24) Rigging Points / M10

SPECIFICATIONS*

• Operating Range	29Hz to 300Hz
• Sensitivity (1W@1M) ¹	99dB
• Power Handling ²	600W (69V) AES/2
• Max SPL (calculated) 1M	127dB Cont. / 133dB Peak
• Nominal Impedance	8 ohms
• Transducers	18" Woofer
• Input	Barrier Strip
• Unit Dimensions	30" H x 26" W x 25" D (76.2 x 66.04 x 63.5 cm)
• Net Weight	43.54 kg (96 lbs)
• Shipping Dimensions	33.1" x 29.9" x 28.3" (84 x 76 x 72 cm)
• Shipping Weight	145.5 lbs (66 kg)
• Enclosure	13 ply Baltic birch / (16) Rigging Points / M10
• Finish Options	Flat Black Latex

APPLICATIONS

- Developed for high-performance cinema applications where the highest quality and intelligibility of sound is required
- Cinema systems extreme low frequency support for bass management in Atmos installations

*Due to product improvement research, SLS Audio reserves the right to make changes to existing products without notice.

1. A sine wave sweep is applied to a voltage level measured at the loudspeaker terminals corresponding to 1W@1M as referenced to the loudspeaker's nominal impedance and the measuring distance. SPL is measured in an anechoic environment in the loudspeaker's far field, with the exception of subwoofers, which are measured in half space. Sensitivity is determined by a Log/Log averaging method from 315Hz to 16kHz in the anechoic environment. Subwoofers use the same method with the half space measurement, but within their specified operating bandwidth.

2. AES established in accordance with AES/2-2012 standard.



Dolby Laboratories, Inc. 1275 Market Street, San Francisco, CA 94103-1410 USA dolby.com

Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories.
© 2018 Dolby Laboratories, Inc. All rights reserved.