



## SLS CSB215-CM Cinema Screen Channel Low-Frequency Module



CSB215-CM shown with  
CS300MH-CM  
mid/high-frequency module

The CSB215-CM is a mid/bass cinema loudspeaker. Its primary application is for use as a companion to the CS200MH-CM/CS300MH-CM mid/high enclosures in medium to large-sized theatres.

The 15" long excursion, bass loudspeakers have been specifically designed to deliver high-impact bass response.



# SLS CSB215-CM Cinema Screen Channel Low Frequency Module

## KEY FEATURES

---

- Powerful magnet assembly
- Open and clear sound at high SPL due to advanced transducer technology
- 13-ply 3/4" Baltic Birch cabinet construction
- Barrier strip input connection

## SPECIFICATIONS\*

---

• Operating Range	40Hz to 800Hz
• Sensitivity (1W@1M) <sup>1</sup>	98dB
• Horizontal Coverage	-
• Vertical Coverage	-
• Power Handling	900W (60V) AES/2
• Max SPL (calculated) 1M	128dB continuous/134dB peak
• Nominal Impedance	4 ohms
• Crossover Frequency	-
• Transducers	LF 15" x 2
• Input	Barrier Strip
• Dimensions	83.82 cm (33") H 58.42 cm (23") W 38.1 cm) 15"D
• Enclosure	13 ply Baltic birch
• Net Weight	37.65 kg (83 lbs.)
• Rigging	Attachment Points for CS300MH-CM & CS200MH-CM
• Accessories	-
• Finish Options	Flat Black Latex

## APPLICATIONS

---

- Developed for high-performance cinema applications where the highest quality and intelligibility of sound is required
- Behind Screen LCR

\*Due to product improvement research, SLS Audio reserves the right to make changes to existing products without notice.

1. A sine wave sweep is applied to a voltage level measured at the loudspeaker terminals corresponding to 1W@1M as referenced to the loudspeaker's nominal impedance and the measuring distance. SPL is measured in an anechoic environment in the loudspeaker's far field, with the exception of subwoofers, which are measured in half space. Sensitivity is determined by a Log/Log averaging method from 315Hz to 16kHz in the anechoic environment. Subwoofers use the same method with the half space measurement but within their specified operating bandwidth.

2. AES established in accordance with AES/2-2012 standard.